



# WHITLOCK-MATERIAL HANDLING

## AC AND ACM SERIES COMPRESSED AIR DRYERS



**ACM30/3.0 Machine  
Mount Dryer with Hopper**



**ACM30F Floor Model Dryer**

### STANDARD FEATURES

- Standard temperature range: 110°F to 300°F  
High temperature range: 110°F to 400°F
- Compact size with full size performance
- Easy-to-use off-the-shelf microprocessor control provides digital temperature control up to 300°F (400°F high temperature option available)
- Control system complies with NFPA79, UL and CUL for maximum safety, including electrical disconnect and branch fusing
- Standard model (AC Series, no membrane unit) reduces dew point of compressed air supply by 50°F
- Membrane option (ACM Series) maintains -40° dewpoint in all environments
- Cabinet style design for maximum safety
- Instant -40°F dewpoint with ACM dryers
- No temperature spikes, no regeneration or process blowers, no desiccant, no regeneration heaters, no moving parts
- Stainless steel heater boxes
- High-efficiency 0.01 micron filter assembly (no contamination, can be mounted inside clean room)
- Safety switch and alarm to monitor air supply
- 30 and 60 CFM models available (50 and 100 m<sup>3</sup>/hr)
- Premium quality Incoloy® low watt density heaters for dependable service
- CE models available
- 460/3/60 supply voltage—others available



1100 E Woodfield Road  
Schaumburg, IL 60173 USA  
Tel. 847-273-7700 Fax 847-273-7804





# WHITLOCK-MATERIAL HANDLING

## AC AND ACM SERIES COMPRESSED AIR DRYERS



**The dryer is available mounted on a portable cart for additional convenience.**

### OPTIONS

- Casters
- High temperature (400°F) package
- Dew point monitor
- CE models available
- Portable cart

### MACHINE MOUNT MODELS INCLUDE

- 1.7, 3.0, 4.0 or 6.0 cu. ft. (50, 85, 110, or 170 liter) stainless steel drying hopper
- Machine mount adapter with drain
- Interconnecting hose and clamps

### FLOOR MOUNT MODELS INCLUDE

- 12' high-temperature silicone hose and clamps for process air
- Rubber feet

### ADDITIONAL FEATURES



All AC and ACM control systems include an electrical disconnect and branch fusing for maximum safety.



The microprocessor controller features digital temperature control.

### STANDARD CONTROLLER FEATURES

- Off-the-shelf 1/16 DIN temperature controller
- Programmable relay (PRC) based control system
- Enclosure meets NFPA 79, UL and CUL electrical standards
- Non-fused disconnect
- High process temperature alarm light

### OPTIONAL CONTROLLER FEATURES

- Audible alarm with silence button
- Digital dewpoint monitor -40°F



1100 E Woodfield Road  
Schaumburg, IL 60173 USA  
Tel. 847-273-7700 Fax 847-273-7804

